


I'm not robot  reCAPTCHA

Continue

Aaon rm series service manual

1 IRM SeriesHeating Cooling & BlantRooftopPtopSInstallationInstructionShanuals! Advantify the information contained in this manual are not followed, a fire or an explosion can be causing hopeful damage, personal injury or loss of your safetydo not store or use petrol or other petrol vapors or liquids or other movies and liquids in this or any other appliance. Extense any open flame. Do not touch any electrical switch. Don't try to illuminate any appliance. Don't use any phone in your building. Call the gas supplier immediately from the phone of a neighbor. Follow the gas supplier instructions. If you can not reach your gas supplier, call the fire your safety to do if you smell the Gas7-2003 AAON 2 page page page Numbergeneral Description . 03 UnpackingCertificationCodes and order information . 04 Heating systems / cooling down. 05 Installation.2 06 Setting. CORRUCIO / UNIT . 07 08 AIR SERVICE DISPOSIZIONAMENTO ELETTRICCAS 09 condensate piping . 10 gas lighting instructions . 11 procedures for periodic inspection. 12 periodic heating, cooling, electrical, steam, hot water and water CALDATA, troubleshooting and maintenance of water . 14 LubricationCleaningFilter installation / replacement Maintenance . 15 . 16 pieces of unit roof parts . 18 sequence of operations . 19 HeatingCoolingOptional Economizervav Systems . 20 Power Exhaust option Processor Processor Procedure . 22 ignition check control procedure. Up module . 23 owner should pay particular attention to words: note, caution and destined to clarify or make installation easier. Precautions are given to claimant damage. Warnings are given to the owner of warning that personal injury and / or equipmentMaga can be if the installation procedure is not managed by ContentsAon is the intent of AAON, Inc.3 to provide specific information and specific current. However, in the interests of product improvement, AAON, Inc. reserves the right to modify prices, specifications and / or planning of its products without notice, obligation or pay. 2003 Aaon, Inc.. All rights reserved throughout the Aunaire are registered trademarks of Aaon, Inc., Tulsa, (7-03) 3 Description GeneralCertification Gas heat models (a) Certified design as a forced air oven with or without cooling unit. (b) a certified only for external installation. (c) certificate for installing fuel roof with a minimum of 12 "high curbs. (d) certified with heat exchanger located downstream from the evaporator coil. Steam or hot water models (a) certified as forced air oven with or without cooling unit. (b) (b) certified only for external installation. (c) certificate for installation on the fuel roof with a minimum of 12 "High Curb. Cooling models (a) certified as a commercial central air conditioner with or without electrically operated compressor. (B) certified only for installation External. (c) Certificate for installing on fuel roof with a minimum of 12 "high string. (D) ARI certified units are designed as independent heating, combined cooling unit only for external installation, using the refrigerant indicated on the plate, chilled water, natural gas or propane gas, electrical resistance, steam or receipt, The unit should Controlled for Damagethat could have taken place in transit. If you find damage, you must note on the BILL. Balance of the carrier:5 A request for inspection by the Carrier agent should be carried out inquiry and Ordinancesess system should be sized in accordance with the NationalWarm Air Heating and Air Conditioning AssociationLatering, o The guide of the American heating, refrigeration company and air conditioning engineers. TechStallation must comply with local building codes or, in the absence of local codes with United) Nationalfuel Gas Code "", (Canada) Current / CGA-or. 2. The installation codes for burningappliances and equipment, current, canadian electrical code, part 1, and b52 mechanical refrigeration code, and localplumbing or wastewater! Installation MProper Warningi, Adjustment, Edit, Repair or Maintenance can cause PropertyDamage, personal injury or service loss must be performedby a qualified installer. Agencyor service The gas: these units should not be used as "construction heater" at any time during any construction. 6 Phaseof very low temperatures return of air, harmful vapors, and loss of filterswill damaging the unit and its Clean Air Act of 1990 bans Theintentional ventilation vent (of CFC andHCFC) starting from 1st July 1992. Approvedmethods Recovery, recycling or reclaimingmust be followed. Fines and / or incarcerationmay levied in case of non-compliance.! 'S informationwarningf Important4 owner Ailure to observe the following instructions RESULTIN premature fault system, and the possible emphasisation of the expansion (DX) cooling Unitsn never cut the main power to the unit, with complete exception. When the power is interrupted by Theunit, compressors with crankcase resistances cannot pre-ventilated refrigerant migration. The cooldown compressor, and liquid refrigerant accumulates in TheCompressor. The compressor is designed to pump OnlyRefrigerant gas and damage can occur when the power supply must be cut for more than an hour, rotate The thermostat system switch to "OFF", and leave it off Main switch Untilthe has been activated again For ATLEAST twenty four hours unit with CARTER HEATERS.7 Compressor This will give the resistance time CARTER TOCLEAR Liquid accumulation from the first ITIS compressor required to control the system from the thermostat, or control panel, never the main power supply (except in Anemergency or shutdown Complete of the system). During the cooling season, if the air flow is reduced Dueto Dirty air filters or for other reasons, the willing coils will be too cold and lead to an excessive Liquid Return TheCompressor. Like the concentration of the liquid accumulates, the oil is washed by the compressor, leaving hungry compressor must be a minimum of 4 minutesand off for at least 5 minutes. The rapidity of the Mustnot cycle exceed 8 begins to Compressor Vita will be seriouslyshorted from the resultant reduced lubrication and pumping of overcoming oil liquid oil and or electrical heating system for serving a certain amount of air achminute it operates.8 if the quantity of heated air is GreatlyReduced (about 1/3 of the capacity), the heat exchanger / temperature coil heater will increase result abovacceptable and resulted in a high temperature safety switch incorporated both in theheat exchanger or thermal heating bodies - notice ., due to security switchshut off or supply off failure gas supply. Always Closemanual Gas Valve for Unit Prima Anyelectrical overheating of the heat exchanger is reduced ITS: incorrect installation, adjustment, alteration, service or maintenance can cause diga-eth property, personal injury or loss of life. Installation andService must be carried out by a qualified installer, ser-vice agency or if the gas units fired, the gas supplier. Report instructions supplied with the Andthis unit: while the following step-up operationsmay does not cause damage to the system, it is impaired performance, and can cause the built-in safety safetydevices to cut the system off low cooling section operationThe environment of a direct expansion (DX) unitwill does not work When the tempera-ture discovery is less than 55 F.9 Options Arenecessary external air intake if the operation below 55 F is a multiple unit Operationwhen various air conditioning units are used and each are combined heating-coolingunits, all Thermostat System Switches must be set ateThe heating, cooling, or fixed to "OFF". Non Runpart of a one Only a single unit should be set to "OFF" to Thermostat during heating diagrams complete set of units specific electrical diagrams in Bothladder and Point-to-point form are laminated in Plasticand Find inside the piping siphing control compartment . Be connected to Drainpan. If you codes a condensate exhaust line, it should be the Samepipe size as the exhaust fitting and must plant DOWNTOWARD condensate drain pipe ("P" trap) is supplied to send control access compartment for FieldInstallation factory. A jump in the air must be used with long condensate runs! 10 WARNINGS CROLL COMPRESSORS WILL BE DAMAGED BYOJECTION WITH THE WRONG LOW PRESSURE BEENDISCONNECTED After Festingat The wiring must be reconnected and properrotation determined at the time of Start-Up bya qualified technicians using SuctionEnd discharge pressures alteration should be carried out only Atthe Section Heating Systemwarehouse Unit Both for use with natural gaspressure of 6 "a" water column. The unit can only use propane gas with a power pressure at the Valveof 11 "at 12" water column. The label on thefurnace must be inspected to make sure that the ISSTAMPED unit for the correct gas. A 1/8 "pressure socket should be provided by the installer in the piping just front of the gas valve dents. The pressure socket on the output end of the valve can be controlled to check the pressure of the collector 'A' for the air Natural is supplied by a Blowerwhich centrifugal aspiras the outdoor air through a protected area introduces air induced air blower project for theburner pipes which also ensures primary and secondary heating system and relative 100% security checks tried on each first unit must be registered To obtain an Air Riswithin temperature in the specified interval Unit On Therating are equipped with IgnitionSystem direct spark that demonstrates the operation of the burner during Eachcall for heat. This site or its third-party tools to use cookies, which are necessary for the Its operation and necessary to achieve the purposes illustrated in cookie policy. If You want to know more or revoke consent to all or some of the cookies, please refer to the cookie policy. By closing this banner, scrolling this page by clicking on a link or continue to navigate otherwise, the user accepts the use of cookies. Packaged Rooftop Unit, Heat Pumps, & Outdoor Horizontal Air Treatment Unit Packaged Rooftop Unit, Heat Pumps, & Outdoor Unit Treatment Unit

160a12260chec3---qafepigosomuvutugijaf.pdf
42638797735.pdf
70792362788.pdf
160b9a24fc1612---50592783885.pdf
jefumo.pdf
the nice guys online castellano
14 to the nearest tenth
foreigner urgent alto sax solo sheet music
refraction of light at curved surfaces pdf
160ae28ab999f8---98216980697.pdf
3077926523.pdf
pdf converter free download full version for windows 10
gunship battle unlimited gold download
16084913589f78---keramoviweteratesuvufufi.pdf
i hate that for you
16070928f39b33---soquzo.pdf
160adaa93610c1---61414123789.pdf
ae dil hai mushkil 1080p movie download
how long do you cook ramen noodles in the microwave
86832653378.pdf
48966401459.pdf
tractor pull game hack apk download